

BORNAS DE CONEXIÓN



- Código Prodin: 220284
- Descripción: Borna unipolar (1V) 20/25 AMP naranja PSB4-01P FK

- Código Prodin: 220274
- Descripción: Borna bipolar (2V) 16/20 AMP naranja PS 2,5-02P FK

- Código Prodin: 220279
- Descripción: Borna tripolar (3V) 16/20 AMP naranja PS 2,5-03P FK

MATERIAL	1 POLO	2 y 3 POLOS
Pitch	13,1 mm	10 mm
Screw	M4,0 Steel Zinc Plated	M3.5 Galvanized Steel
Terminal	Brass or Steel Tin Plated	Tin Plated Brass
Housing	PA66 UL94V-0	Pa66 UL94V-0
CAPACIDAD		
Rated Voltage	600V	750V
Rated Current	25A	30A
Withstand Voltage	AC2500V/1Min	AC2000V/1Min
Wire Range	20-12 AWG	24-8 AWG
Temperature Limit		
Max Soldering		
16 Ampers		
30 Ampers		



Prodin Ferrite S.L.

Polígono Industrial "Molí dels Frares" Calle C/A - Nave 2
08620 Sant Vicenç dels Horts - Barcelona - España
T: +34 936 724 610
info@prodinferrite.com - www.prodinferrite.com

